



MAINTENANCE SCHEDULE 1995-1997 RANGE ROVER

Owner's Name: _____

Date: _____ Mileage _____ RO#: _____

| MAINTENANCE INTERVAL | TIME (Months) | 6 | 12 | 18 | 24 | 30 | 36 | 42 | 48 |
|----------------------|------------------------|-----|----|------|----|------|----|------|----|
| | MILES (Thousands) | 7.5 | 15 | 22.5 | 30 | 37.5 | 45 | 52.5 | 60 |
| | KILOMETERS (Thousands) | 12 | 24 | 36 | 48 | 60 | 72 | 84 | 96 |

VEHICLE EXTERIOR

| | | | | | | | | | |
|---|--|--|--|--|--|--|--|--|--|
| Add 16 oz Land Rover Fuel Conditioner (LRN10500) | | | | | | | | | |
| Inspect wiper blades | | | | | | | | | |
| Lubricate door locks, check straps | | | | | | | | | |
| Lubricate hood latch and safety catch, fuel door hinges | | | | | | | | | |

VEHICLE INTERIOR

| | | | | | | | | | |
|---|--|--|--|--|--|--|--|--|--|
| Check parking brake (Adjust if necessary) | | | | | | | | | |
| Check seat belts | | | | | | | | | |

UNDER HOOD

| | | | | | | | | | |
|-------------------------------------|--|--|--|--|--|--|--|--|--|
| Inspect coolant hoses | | | | | | | | | |
| Inspect radiator and AC condenser | | | | | | | | | |
| Replace pollen filters | | | | | | | | | |
| Check power steering fluid level | | | | | | | | | |
| Check brake fluid level | | | | | | | | | |
| Change brake fluid | | | | | | | | | |
| Change engine coolant | | | | | | | | | |
| Replace spark plugs | | | | | | | | | |
| Replace air-cleaner element | | | | | | | | | |
| Clean and service battery | | | | | | | | | |
| Inspect steering intermediate shaft | | | | | | | | | |
| Inspect serpentine drive belt | | | | | | | | | |
| Replace serpentine drive belt | | | | | | | | | |
| Service evaporative loss system | | | | | | | | | |

UNDER VEHICLE

| | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|
| Change engine oil and replace filter | | | | | | | | | |
| Inspect exhaust system and heat shields | | | | | | | | | |
| Inspect tires | | | | | | | | | |
| Inspect brake lines | | | | | | | | | |
| Inspect brake pads, calipers and discs | | | | | | | | | |
| Lubricate drive shafts and U-joints | | | | | | | | | |
| Inspect steering rods, joints and dust covers | | | | | | | | | |
| Inspect shock absorbers | | | | | | | | | |
| Inspect suspension links and mountings | | | | | | | | | |
| Inspect wheel speed sensor wiring | | | | | | | | | |
| Inspect fuel lines | | | | | | | | | |
| Inspect Electronic Air Suspension system | | | | | | | | | |
| Service Electronic Air Suspension system | | | | | | | | | |
| Change transfer gearbox oil | | | | | | | | | |
| Change front and rear axle oil | | | | | | | | | |
| Change transmission fluid | | | | | | | | | |
| Replace transmission fluid filter | | | | | | | | | |
| Replace fuel filter | | | | | | | | | |
| Replace oxygen sensors and reset service reminder | | | | | | | | | |
| Record performance of Service in Passport to Service | | | | | | | | | |

REQUIRED EMISSION MAINTENANCE

SUPPLEMENTARY RESTRAINT SYSTEM (SRS): The AIR BAGS in the SRS must be replaced EVERY TEN YEARS

NOTIFICATION OF SERVICE REQUIREMENTS:

- ◆ Your next service is due in six (6) months or 7,500 miles (12,000 km), whichever is sooner.
- ◆ Please refer to your owner's manual for **Service Recommendations** if your vehicle is used extensively off-road, or under severe conditions.
- ◆ The owner or operator is responsible for **Owner Checks** listed in the Owner's Manual. These are *not* included in the Service Schedule.